

Listing of: CM408213 (C:\WINDYN\901\DATA\CM408213.SFD)
 Channel Group: Corrected Torque and Power Page 1 of 1
 Printed on Nov 28, 2007 at 14:41:15
 Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	VolEff %	Fuel A lb/hr	Fuel B lb/hr	BSFC lb/hph	WtrOut degF	OilOut degF
	3900	445.0	330.4	0.0	88.2	62.4	0.479	136	0
	4000	451.2	343.6	0.0	86.7	64.1	0.461	137	0
	4100	464.0	362.2	0.0	86.1	70.4	0.454	137	0
**	4200	469.7	375.6	0.0	89.7	76.4	0.465	137	0
	4300	474.9	388.8	0.0	90.7	79.6	0.461	137	0
	4400	481.0	403.0	0.0	92.1	82.0	0.455	136	0
	4500	488.9	418.9	0.0	94.0	85.7	0.451	136	0
	4600	489.4	428.6	0.0	92.8	86.4	0.438	136	0
	4700	482.9	432.2	0.0	94.6	86.6	0.440	136	0
	4800	500.1	457.1	0.0	101.1	94.8	0.450	136	0
	4900	500.2	466.7	0.0	107.2	96.2	0.459	136	0
	5000	498.9	474.9	0.0	106.8	98.9	0.456	136	0
	5100	494.6	480.2	0.0	113.7	102.2	0.474	136	0
	5200	490.0	485.2	0.0	111.6	103.9	0.468	136	0
	5300	494.7	499.2	0.0	118.6	103.7	0.469	136	0
	5400	484.0	497.6	0.0	121.3	108.2	0.485	136	0
	5500	476.9	499.4	0.0	119.3	107.5	0.478	136	0
	5600	472.2	503.5	0.0	119.0	107.6	0.474	135	0
	5700	473.4	513.8	0.0	126.1	114.2	0.493	135	0
	5800	465.1	513.6	0.0	126.8	107.7	0.482	136	0
	5900	450.9	506.5	0.0	123.5	111.4	0.489	136	0
	6000	443.2	506.3	0.0	127.7	112.5	0.500	136	0
	6100	440.8	512.0	0.0	132.5	111.3	0.502	137	0
**	6200	434.3	512.7	0.0	130.8	118.9	0.515	136	0
	6300	423.8	508.3	0.0	135.8	125.4	0.544	135	0
	6400	417.2	508.4	0.0	133.4	125.6	0.539	136	0
	6500	409.3	506.5	0.0	132.1	126.0	0.539	136	0
	6600	400.7	503.6	0.0	142.0	123.9	0.560	136	0
	6700	392.7	501.0	0.0	132.9	131.5	0.561	136	0
	6800	378.6	490.2	0.0	134.7	139.4	0.594	136	0
	6900	370.1	486.2	0.0	115.7	134.5	0.547	136	0
	7000	361.0	481.2	0.0	129.1	135.4	0.585	136	0
	7100	354.7	479.5	0.0	137.4	137.3	0.609	137	0

**Range: 4200 RPM - 6200 RPM

AVG:	5200	476.5	470.3	0.0	111.4	99.8	0.472	136	0
MIN:	4200	434.3	375.6	0.0	89.7	76.4	0.438	135	0
MAX:	6200	500.2	513.8	0.0	132.5	118.9	0.515	137	0

1014